

**Application**

Aluminium pole with base plate.  
Cylindrical pole with static strength in accordance with EN 40.

**Product description**

Luminaire pole made of aluminium alloy and aluminium, powder coated and lacquered  
Pole top  $\varnothing$  76 mm  
Base plate with 4 fixing holes for installation on a foundation or anchorage unit – accessory 70 899 –  
With inserted door made of aluminium  
Door latch – square spanner – wrench size 8 mm.  
C-clamp with earth conductor connection and 2 sliding nuts M6 to accommodate a connection box according to DIN 43628 / VDE 0660

**CE** – Conformity mark

Wind catching area: 0.46 m<sup>2</sup>

Weight: 21.4 kg

**Accessories****Connection boxes**

– Cable box IP 54  
2 fuse Neozed 6 A  
3 inputs for cable 5 x 10<sup>□</sup>  
2 outputs for cable 3 x 1.5<sup>□</sup>

– Cable box IP 54  
2 fuses Neozed 6 A  
2 inputs for cable 5 x 10<sup>□</sup>  
2 outputs for cable 3 x 2.5<sup>□</sup>

– Cable box IP 54  
3 fuses Neozed 6 A  
3 inputs for cable 5 x 16<sup>□</sup>  
2 outputs for cable 5 x 2.5<sup>□</sup>

